



MANOR OAK

A rustic, white washed and hand scraped product, may contain knots and cracks. This product must be oiled after installation and prior to use.

| PRODUCT DETAILS | | FACTS | | TECHNICAL PROPERTIES | | |
|--------------------|--|---------------------|---------------------|----------------------------|-------------|-------------|
| Article Number | 201XABEKFVKE280 | Wood Species | Oak | Moisture content | EN13183 | 7%±2% |
| Surface Treatment | Oil | Design | 1-strip | Minimum Mean Density kg/m³ | | |
| Refining Treatment | Bevelled 4-sided, Brushed, Handscraped | Grading | Variation (Town) | >500 kg/m³ | | |
| Dimensions | 2800 x 260 x 20 mm | Range | Kährs Supreme | Reaction To Fire | EN13501-1 | Dfl-s1 |
| Weight per Package | 38 kg | Collection | Grande Collection | Formaldehyde Emission | EN717-1 | E1 |
| Area per Package | 2.91 m² | Natural/Stained | Stained | Content PCP | CEN/TR14823 | ≤ 5 x 10-6n |
| Area Per Board | 0.728 m² | Joint | Tongue & Groove | Breaking Strength N/mm² | EN1533 | NPD |
| DETAIL DESCRIPTION | | Floor heating | No | Thermal Conductivity | EN12664 | 0,125 W/mK |
| | | Wear-layer material | Hardwood | Thermal Resistance R-Value | | |
| | | Thickness | 20 mm | .16 (m2K/W) | | |
| | | Installation method | Glue-down, Floating | Biological Durability | EN350-2 | Class 1 |
| | | Surface Colour | White | CARB2 | | |
| | | | | Compliant | | |

COLOUR CHANGE

Stained product - noticable color change over time.

CERTIFICATES

